

# ZD888TA 4-Inch Desktop Printer

## Remarkable value, quality printing, simple operation

When your budget requires a basic printer, that usually means compromising on quality, functionality and performance — value printers typically use less expensive components and offer fewer features. The result is a printer with a shorter lifecycle that falls short of your performance expectations, requiring repairs and replacement more frequently, ultimately costing you more instead of less. Meet the value printer that's different — the Zebra ZD888TA. With this 4-inch thermal printer, there's no compromise. You get a printer that delivers the same quality that has made Zebra an industry leader. This printer is built to last for years. It's easy to install and operate. You can count on highly legible print quality for every single label — regardless of whether you choose 203 dpi or the new 300 dpi option. This USB printer is up and running in an instant. Just plug it into any USB port and plug in the power cord and you're ready to print. And regardless of how many shifts you operate, you can count on reliable performance, every minute of every shift.



## Designed for Simplicity

### Start Printing in Minutes

This USB label printer is simple to install — you can start printing nearly instantly, right out of the box. And since this printer supports ZPL, EPL and non-Zebra command languages, you can easily replace the printer you're using today.

### Media is Easy to Manage

The transparent media window lets workers instantly see how much media is left and when to change the roll to prevent workflow disruptions. The OpenACCESS™ clamshell design makes it easy to access and replace media.

And if you print a high volume of labels, a 300 m ribbon roll means fewer changes and improved worker productivity.

### Easy Everyday Operation

The ZD888TA is so intuitive that practically no training is required. With a single button for feed and pause, this printer couldn't be easier to operate. A single green/yellow/red LED makes it easy to see printer status at a glance. And whether you need to open the printer, feed labels or change the ribbon, color-coded touch points make it simple.

### Automatically Resumes Operation After a Power Outage

With this new time-saving feature, there's no need to physically turn on your printers after a power interruption — ideal for printers that may be difficult to reach or locked in a cabinet for security. And the power switch is located near the back of the printer to prevent workers from accidentally turning the printer off.

## The Right Options

### Fast Printing with Your Choice of Resolution

With a print speed of 6 inches per second, this 4-inch barcode printer keeps pace with your business and your workflows — your workers won't be waiting for labels to print. And with a choice of 203 dpi or 300 dpi, you get a very versatile printer that provides the resolution you need on the types of items you print — from prescription, specimen, IV bag and food information labels to patient ID wristbands and packing slips, asset and inventory labels and more.

**The quality, features and performance your business needs, at a price you can afford.**

For more information, please visit [www.zebra.com/zd888](http://www.zebra.com/zd888)

### **More Flexibility with a Moveable Sensor**

The moveable media sensor supports almost any size label, allowing your ZD888TA printer to support a wide variety of applications.

## **Complimentary Software Makes Printer Setup and Label Creation Easy**

### **Zebra Setup Utilities**

Easily set up, configure and manage your Zebra printers through a user-friendly, intuitive interface with this free application. Whether you're adding a new printer, moving an existing printer to a new location or adding new capabilities, easy-to-use wizards make it simple. Just click to configure the printer and select the best speed and darkness combination for your media. The printer driver automatically installs itself. And Quick Tools provides instant access to the most common printer diagnostic tools, making it easy to test and confirm configurations and control printer functions.

### **ZebraDesigner Essentials**

Easily design, edit and print labels, tags and receipts with this free tool. No knowledge of barcoding or labeling is required. The Windows®-based intuitive Microsoft Office-style interface is so easy to use that training is virtually eliminated. Start with a pre-designed label that includes text, a barcode and graphics or create a label from scratch in minutes. And the tool supports 20 languages.

## **Keep Your Printers Up and Running with the Right Service Plan and Certified Supplies**

### **Backed by Zebra's worldwide service and support**

You count on your printers to keep your operations moving. And with an optional Zebra OneCare™ Maintenance Plan, it will. You get unmatched support, directly from the company that knows your printer best — Zebra. Access repair support services, live-agent technical support and software support quickly anywhere around the globe through Zebra and its trusted network of more than 10,000 partners. Zebra OneCare™ provides enhanced coverage that exceeds standard warranty for normal wear and tear, priority repair turnaround times at the depot and more—all for a tiny fraction of the cost of a single repair.

### **Consistently Exceptional Zebra Certified Supplies**

Printing supplies can impact everything from printhead lifespan to operational efficiency. That's why we design, produce and rigorously pre-test our own line of thermal printing supplies to ensure that your Zebra printer delivers consistent, optimized performance. For industry-leading quality, service and thermal printing expertise, choose Zebra Certified Supplies.

# Specifications

## Standard Features

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"><li>• Thermal Transfer or Direct Thermal print method</li><li>• ZPL and EPL programming languages</li><li>• Single LED status indicator</li><li>• Single button for feed/pause</li><li>• USB connectivity</li><li>• OpenACCESS™ for easy media loading</li><li>• Dual-wall frame construction</li><li>• ZebraDesigner Essentials -for more information or to download the easy label design tool free, please visit <a href="http://www.zebra.com/zebradesigner">www.zebra.com/zebradesigner</a></li><li>• Two-year standard warranty</li></ul> |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Physical Characteristics

|            |                                         |
|------------|-----------------------------------------|
| Dimensions | ZD888TA: 267 mm L x 202 mm W x 192 mm H |
| Weight     | ZD888TA: 1.8 kg                         |
| Color      | Gray or white color scheme              |

## Printer Specifications

|                     |                                                                                                                                 |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Resolution          | 203 dpi/8 dots per mm<br>300 dpi/12 dots per mm (optional)                                                                      |
| Memory              | 8 MB Flash; 16 MB SDRAM                                                                                                         |
| Maximum Print Width | 104 mm for 203 dpi<br>106 mm for 300 dpi                                                                                        |
| Maximum Print Speed | 152 mm per second for 203 dpi<br>127 mm per second for 300 dpi                                                                  |
| Media Sensors       | Movable black mark sensor, limited range from center to left side; fixed off-center gap sensor; ribbon sensor; head open sensor |
| Firmware            | ZPL II; EPL 2; XML                                                                                                              |

## Media and Ribbon Characteristics

|                                    |                                                                                                                         |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Label Length                       | Minimum: 25.4 mm; maximum: 990 mm                                                                                       |
| Media Width                        | 25.4 mm to 112 mm                                                                                                       |
| Media Roll Size                    | Maximum outer diameter: 127 mm<br>Core inner diameter: 12.7 mm and 25.4 mm standard and 38.1 mm using optional adapters |
| Media Thickness                    | Minimum: 0.06 mm<br>Maximum: 0.1905 mm                                                                                  |
| Media Types                        | Roll-fed or fan-fold; die cut or continuous with or without black mark; tag stock; continuous receipt paper; wristbands |
| Ribbon Types                       | Wax; wax/resin; resin                                                                                                   |
| Ribbon Outside and Inside Diameter | Outer: 34 mm, 63.5 mm<br>Inner: 12.7 mm, 25.4 mm                                                                        |
| Ribbon Length                      | 74 m to 300 m                                                                                                           |
| Ribbon Ratio                       | 1:4 ribbon to media (300 m)<br>1:1 ribbon to media (74 m)                                                               |
| Ribbon Width                       | 33.02 mm to 110 mm                                                                                                      |

## Options and Accessories

|                 |          |
|-----------------|----------|
| Communication s | USB only |
| Media Handling  | None     |
| Real-time Clock | None     |

## Fonts/Graphics/Symbologies

|                   |                                                                                                                                                                                                                                                                                         |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1D Barcodes       | Code 11, Code 39, Code 93, Code 128, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2-or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, Planet Code                                                           |
| 2D Barcodes       | Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, MicroPDF, Aztec                                                                                                                                                                                                              |
| Fonts and Graphic | 16 resident expandable ZPL II bitmap fonts; Three resident scalable ZPL fonts; Five resident expandable EPL2 fonts; Native open-type font support; Unicode compliant for multi-language, on demand thermal printing; 2 MB user available non-volatile memory, 2 MB user available SDRAM |

## Regulatory

|                     |
|---------------------|
| CCC; BSMI; KCC; BIS |
|---------------------|

## Printers Supplies

|                                                                                                                                                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| For industry-leading quality, service and thermal printing expertise, choose Zebra Certified Supplies to ensure consistent, optimized performance for your Zebra printer. |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Recommended Services

|                                                                                                                                        |
|----------------------------------------------------------------------------------------------------------------------------------------|
| Zebra OneCare Essential; for more information, please visit <a href="http://www.zebra.com/zebraonecare">www.zebra.com/zebraonecare</a> |
|----------------------------------------------------------------------------------------------------------------------------------------|

## Printer Software

|                                                 |
|-------------------------------------------------|
| Zebra Setup Utilities; ZebraDesigner Essentials |
|-------------------------------------------------|

## Product Warranty

|                                                                                                                                                                                                                                                                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ZD888 Series printers are warranted against defects in workmanship and materials for a period of 2 (two) years from the date of shipment. For the complete warranty statement, please visit <a href="http://www.zebra.com/warranty">www.zebra.com/warranty</a> |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

# Markets and Applications

## Manufacturing

- Shipping label
- Dangerous goods label
- Receiving label
- Agency label
- Packing list
- Inventory label
- Asset tag

## Transportation and Logistics

- Shipping/receiving label
- Packing slip
- Asset label

## Retail

- Shelf label
- Buy online pick up in store label
- Price markdown
- Return tag
- Asset and inventory label
- Food safety label
- Receipts
- Pharmacy label

## Healthcare

- Specimen collection
- Prescription label
- Patient ID wristband
- Blood/IV bag label
- Patient records
- Asset label

# Operating Characteristics

|                       |                                                                            |
|-----------------------|----------------------------------------------------------------------------|
| Operating Temperature | 5° C to 40° C                                                              |
| Storage Temperature   | -40°C to 60°C                                                              |
| Operating Humidity    | 25% to 85% non-condensing                                                  |
| Storage Humidity      | 10% to 90% non-condensing                                                  |
| Electrical            | Auto-detectable (PFC compliant) 100-240VAC; 50-60Hz; ENERGY STAR qualified |



**NA and Corporate Headquarters**  
+1 800 423 0442  
[inquiry4@zebra.com](mailto:inquiry4@zebra.com)

**Asia-Pacific Headquarters**  
+65 6858 0722  
[contact.apac@zebra.com](mailto:contact.apac@zebra.com)

**EMEA Headquarters**  
[zebra.com/locations](https://zebra.com/locations)  
[contact.emea@zebra.com](mailto:contact.emea@zebra.com)

**Latin America Headquarters**  
[zebra.com/locations](https://zebra.com/locations)  
[la.contactme@zebra.com](mailto:la.contactme@zebra.com)